

CINI4.0



# CINI4.0 Conference Day

16/06/2022, Gent

## PLCnext : an open source IIOT-ready PLC

Hugo Van Rillaer

[hvanrillaer@phoenixcontact.be](mailto:hvanrillaer@phoenixcontact.be)

# PLCnext Technology

Designed by PHOENIX CONTACT



PLCnext Control



PLCnext Engineer



PLCnext Store



PLCnext Community



Brief overview



PLCnext Control



OPC UA



Redundancy



Functional Safety



Edge Computing



Artificial Intelligence



Security



PLCnext Engineer



PLCnext Store




PLCnext Community



PLCnext Technology

# The reliability and robustness of the classical PLC world

enhances with the openness  
and flexibility of Smart Devices



## Flexibility of Linux plus the Reliability of a PLC




PLCnext Runtime System is based on Linux...

- Open Linux Operating System
- ...but as performant as a “classic” PLC!
- Easy task management
  - Precise synchronization in realtime
  - Cycle-consistent data exchange
  - No Linux knowledge needed



## PLCnext Runtime System Architecture



# PLCnext Runtime System Architecture



- Reduced deployment time through the integration of source software
- Connectivity, security & real-time capability are already implemented
- Future-proof, flexible and secure thanks to continuous updates
- Integration of IEC61131-3, high-level languages and open-source software possible
- Apps from PLCnext Store easy to implement

enhanced performance – Data Consistency

# Global Data Space





Fast and consistent data exchange between user programs, fieldbuses, and system programs. Access via Data Logger, HMI, and OPC UA. Security aspects for user management.



enhanced performance – PLC-typical Real-time Performance

## Execution & Synchronization Manager




The patent-applied-for task handling of PLCnext Technology lets program routines of different origin run like classical IEC 61131 PLC code. Your high-level language programs become automatically deterministic.



PLCnext Technology – Limitless engineering options

# PLCnext Runtime System




- Reduced deployment time through the integration of open-source software
- Connectivity, security & real-time capability are already implemented
- Future-proof, flexible and secure thanks to continuous updates
- Integration of IEC61131-3 and high-level languages like C/C++, C#, Matlab, Java, Python, Go or Rust possible
- Apps from PLCnext Store easy to implement



PLCnext Technology – Limitless engineering options


# PLCnext Runtime System and Container




- Docker images from Docker hub can be used
- Portainer.io can be used for container management
- Apps in Docker format from PLCnext Store easy to implement
- (OCI) Open Container Initiative compatible
- gRPC (Remote Procedure Call (RPC) one API (IP/ Socket Communication) for many programming languages (Python, Java, Node.js, ...)
- Podman as Container Engine preinstalled
- Kubernetes, Docker Engine or balenaEngine can optionally be used

enhanced freedom


# Scalable solutions based on Apps in an open Ecosystem



# Scalable Solutions based on open Ecosystems



# PLCnext Technology



PLCnext Control

Function

Performance

AXC F 1152

AXC F 2152

AXC F 3152

RFC 4072S

BPC 9102S


2021

## Open Control Platform







PLCs in various performance classes including PLCnext Runtime System and accessories for PLCnext Technology



# PLCnext Control AXC F 2152




The image shows the PLCnext Control AXC F 2152 device, a compact industrial PLC. It features a grey metal housing with a front panel containing an SD-CARD slot, a display, and several status LEDs (BF-C, BF-D, SF, BOOT, EXT, RUN, FAIL, DBG, D, E). The device is shown from a three-quarter perspective, highlighting its compact size and industrial design.







Core	Random Access Memory	Temperature
 <b>ARM Cortex-A9 (2x 800 MHz)</b>	 <b>512 Mbytes RAM</b>	 <b>-25°C-60°C</b>
# control tasks (IEC 61131)  <b>32</b>	Min. cycle time (IEC 61131)  <b>1 ms</b>	Security  <b>TPM integrated</b>



# PLCnext Control AXC F 3152




The image shows the PLCnext Control AXC F 3152 device, a grey industrial PLC. It features a top panel with an SD-CARD slot, RUN/STOP/MRESET buttons, and a status indicator. The front panel has a large display area with the PLCnext Technology logo and 'Designed by PHOENIX CONTACT' text. Below the display are several status LEDs labeled BF-C, BF-D, SP, EXT, RUN, FAIL, DBG, and F. The bottom panel has various ports including X1, X2, X3, and X4.

Core	Random Access Memory	Temperature
 <b>Intel ATOM x5-E3930 dual-core</b>	 <b>2 GB DDR4 dual-channel RAM</b>	 <b>-25°C-60°C</b>
# control tasks (IEC 61131)  <b>32</b>	Min. cycle time (IEC 61131)  <b>500 µs</b>	Security  <b>TPM integrated</b>




# PLCnext Control for Edge Computing









PLCnext Control for Edge Computing

# Product Features – EPC 1502




The image shows the PLCnext EPC 1502, a compact industrial edge computing device. It features a silver metal housing with a large heat sink on the front. The front panel includes an antenna, a green terminal block for power, an Ethernet port, a DP port, and two USB ports. The top of the device has the PLCnext Technology logo and 'Designed by PHOENIX CONTACT' text.

Core	RAM	Temperature
 <b>Intel Celeron N3350 (Dual Core)</b>	 <b>2 GB RAM</b>	 <b>0°C-50°C</b>
Storage	Approvals	Features
 <b>32 GB eMMC</b>	 <b>UL, CE</b>	 <b>PLCnext RT Edge Functions</b>











# Product Features – EPC 1522




The image shows the EPC 1522 PLCnext Control for Edge Computing device, a compact, industrial-grade unit with a silver metal casing and a black front panel. The front panel features a green terminal block, an antenna, an Ethernet port, a USB port, and two USB-A ports. The device is shown from a three-quarter perspective, highlighting its compact size and industrial design.


<p>Core</p>  <p>Intel Celeron N3350 (Dual Core)</p>	<p>RAM</p>  <p>4 GB RAM</p>	<p>Temperature</p>  <p>0°C-50°C</p>
<p>Storage</p>  <p>32 GB eMMC + 128 GB m.2 SSD</p>	<p>Approvals</p>  <p>UL, CE</p>	<p>Features</p>  <p>PLCnext RT Edge Functions +Serial Interface</p>




# PLCnext Control RFC 4072S



**Core**




**Intel i5 6300U 2 x 2,4 GHz processor**  
# control tasks (IEC 61131)




**32**

**Random Access Memory**




**4 GB DDR 4 dual channel RAM**

Min. cycle time (IEC 61131)




**500 µs**

**Temperature**




**0°C up to 55°C with fan**

Security



**TPM integrated**

# PLCnext Control RFC 4072R










The image shows the PLCnext Control RFC 4072R device, a grey industrial PLC. The front panel features a color display showing the 'RFC 4072R' configuration screen with fields for 'Projektname', 'PN Controller', 'OPC UA', and 'Redundancy' (set to 'First Primary'). The device has various ports including RUN/PROG, STOP, MRESET, SD-CARD, USB, four LAN ports (LNK LAN 1-4), a SYNC port, and power terminals (0VDC, PE, +VDC).

Feature	Specification
CPU	Intel i5 6300U 2 x 2,4 GHz processor
Random Access Memory	4 GB DDR 4 dual channel RAM
ETH-MAC interface	2 x 1 Gbit, 1 x 100 Mbit switched
Synchronization interface	SFP based
Power supply	Dual interface
Temperature	0°C - 55°C



# PLCnext Control BPC 9102S




<p>CPU</p>  <p>Octa-Core Intel Core™ i7-10700TE</p>	<p>Random Access Memory</p>  <p>16 GB, DDR4 RAM</p>	<p>Temperature</p>  <p>-20°C - 60°C without FAN</p>
<p># control tasks (IEC 61131)</p>  <p>128</p>	<p>Min. cycle time</p>  <p>500 μs</p>	<p>Integrated Safety PLC</p>  <p>1x ARM A8 1x ARM A9</p>




enhanced convenience

# IEC 61131-3 Programming with PLCnext Engineer





The screenshot displays the PLCnext Engineer software interface. The main window shows a simulation of two robotic arms, labeled 'Robot 1' and 'Robot 2', with various joints and sensors. The interface includes a 'Main' and 'Robot' navigation pane, a 'Navigation' pane, and a 'COMPONENTS' pane on the right. The 'COMPONENTS' pane lists various hardware components such as 'Local', 'Autocombit (73)', 'Analog input (7)', 'Digital input and output (1)', 'Analog output (8)', 'Controller (3)', 'Digital input (11)', 'Digital input and output (5)', 'Digital output (12)', 'Function (7)', 'Gateway (4)', 'Pulse width modulation (1)', 'Subnet/Bridge (3)', 'Serial communication (3)', 'Strain gauge (1)', 'Temperature input (8)', 'Analog I Profnet (81)', and 'Inize Profnet (172)'. The software is running on a Windows operating system, as indicated by the taskbar and window titles.

**Use the innovative and easy to use features of PLCnext Engineer.**



PLCnext Engineer

# Complete Integrated System




Speed up your application development



Standard and safety programming in one engineering software

# PLCnext Engineer




## Fully integrated Safety programming

- Individual safety functions can be protected by a verification function
- Background signal path analysis
- Background safe semantic analysis
- Diversely-redundant code generator



enhanced convenience

# MATLAB Simulink





Seamless integration of model-based design & development with MATLAB Simulink.





enhanced convenience

# Programming – C/C++





- C/C++ acc. to standard
- Easy interface to the PLCnext Runtime System
- Support of remote debugging
- Use the tool you are familiar with



enhanced convenience

# Programming – C#



- Development and integration of function blocks with C#
- Dedicated plug-in for Visual Studio.
- Execute C# function blocks in real-time with the eCLR runtime system.



Join and get involved

# PLCnext Community

More about PLCnext Technology



[plcnextcommunity.com](https://plcnextcommunity.com)

Upload or download apps



[plcnextstore.com](https://plcnextstore.com)

Ask a question in the forum



[phoe.co/PLCnextForum](https://phoe.co/PLCnextForum)

Use or share open source code



[github.com/plcnext](https://github.com/plcnext)

Get in touch on LinkedIn



[phoe.co/PLCnextLinkedIn](https://phoe.co/PLCnextLinkedIn)

#PLCnext  
#IamPLCnext




PLCnext Community


Join and get involved  
#IamPLCnext




# PLCnext Technology




PLCnext Technology  
Designed by PHOENIX CONTACT





PLCnext Control



PLCnext Engineer



PLCnext Store



Install unexpected possibilities

Filter

- Rating
- Price
- Type

PHOENIX CONTACT PLCnext Store

SEARCH CONTRIBUTORS HELP LOGIN

Download

AnalogTechnology

Basic Light Control

Modbus RTU

Proficloud Writer

Pump Station Control

## Software Store for Automation

Apps for functional extension of PLCnext Control and PLCnext





PLCnext Technology Ecosystem

# Install extraordinary possibilities



# App Types



	Solution App	PLCnext Engineer 61131 Libraries	Runtime	Function Extension
Description	Automation solution consisting of different components with web pages for parametrization	Works as a part of a PLC program	Runtime or framework for further programming tools / languages	Combinable apps to create a solution
User Skill Level				
Example	Tank and Well Control, Pump Station Control, Proficloud Writer	Analog Technology, CANbus, ComSerial, Modbus TCP, IOL_Basic	Codesys, Python, Java or IEC 61499 ...	MQTT, Protocol 1, 2, 3 Cloud Connector, ...
Remark	Ready to use, without programming	PLCnext Engineer needed	Ready to use for programming	Combination of Apps










PLCnext Store – Install extraordinary possibilities

# New industry experts joined the Community



# PLCnext Community – Global Exchange & Collaboration

<p>More about PLCnext Technology</p>  <p><a href="http://plcnextcommunity.com">plcnextcommunity.com</a></p>	<p>Upload or download apps</p>  <p><a href="http://plcnextstore.com">plcnextstore.com</a></p>	<p>Ask a question in the forum</p>  <p><a href="http://phoe.co/PLCnextForum">phoe.co/PLCnextForum</a></p>	<p>Watch and learn with tutorials</p>  <p><a href="http://phoe.co/PLCnextTutorials">phoe.co/PLCnextTutorials</a></p>
<p>Use or share open source code</p>  <p><a href="https://github.com/plcnext">github.com/plcnext</a></p>	<p>Share your experiences on Instagram</p>  <p><a href="https://www.instagram.com/plcnext">@plcnext</a></p>	<p>Get in touch on LinkedIn</p>  <p><a href="http://phoe.co/PLCnextLinkedIn">phoe.co/PLCnextLinkedIn</a></p>	<p>#PLCnext #IamPLCnext</p>



PLCnext Community

Join and get involved  
#IamPLCnext







# PLCnext Technology




PLCnext Technology   
Designed by PHOENIX CONTACT

 PLCnext Control


 PLCnext Engineer


 PLCnext Store


 PLCnext Community





Become a part of the PLCnext Community!  
#plcnext #iamplcnext


 Ask a question in the forum

 Upload or download apps

 Get technical support in the community

 Watch a video for technical support

 Use or share open source code

 Share your experience on Instagram

**PLCnext Technology**  
The ecosystem for limitless automation

In a rapidly changing world, in which more things are now networked together than there are people, industrial automation is also undergoing a fundamental shift. Classic system structures are developing into cyber physical systems, and future-oriented automation systems must be flexible, open, and networked.

## User Collaboration & Resources

Information, support, and helpful resources about PLCnext Technology including FAQs, forums, tutorials and a GitHub presence



# PLCnext Technology Ecosystem



## enhanced development

Connected coworking



## enhanced convenience

Using your favorite programming tool



## enhanced freedom

Flexible integration of open source software and apps



## enhanced connectivity

Open interfaces and cloud integration





## enhanced performance

Real-time execution across different programming languages



enhanced connectivity – Intelligent Networking

# Integrated OPC UA Server




Data Access, Alarms and  
Conditions, Programs, Historical  
Access, Global Discovery Server




enhanced connectivity – Intelligent Networking

# PROFICLOUD, Public Cloud, Private Cloud – any Cloud!

Implement new IoT-based business models through direct connection to cloud-based services and databases.



Benefit from the seamless integration of Phoenix Contact's PROFICLOUD and the any cloud strategy where the PLCnext Store delivers cloud connectors for every cloud. PLCnext Technology supports any customer cloud implementation – public, private, hybrid - including AWS, IBM, Azure and Alibaba.



enhanced connectivity – Intelligent Networking


## List of Communication Interfaces and API's (incl. App extensions)

Fieldbus protocol	General Communication Interface	API	Inside APP only*
<ul style="list-style-type: none"> <li>▪ Profinet (Profidrive via App)</li> <li>▪ Interbus</li> <li>▪ Modbus TCP and RTU via App</li> <li>▪ Ethernet IP (Adapter)</li> <li>▪ CANbus (CANopen, J1939 and NMEA) via App</li> <li>▪ DALI via App</li> <li>▪ HART via App</li> <li>▪ IO-Link via App</li> <li>▪ Profibus</li> </ul>	<ul style="list-style-type: none"> <li>▪ MQTT via App</li> <li>▪ OPC UA (Server)</li> <li>▪ OPC UA (Client) via App</li> <li>▪ DHCP via App</li> <li>▪ SMTP via App</li> <li>▪ SNTP via App</li> <li>▪ SNMP via App</li> <li>▪ DNS via App</li> <li>▪ DNP3 via App</li> <li>▪ IEC60870-5-101 and -104 protocol via App</li> </ul>	<ul style="list-style-type: none"> <li>▪ gRPC</li> <li>▪ REST</li> <li>▪ ANSI-C</li> <li>▪ RSC</li> </ul>	<ul style="list-style-type: none"> <li>▪ BacNet IP</li> <li>▪ Enocean (EVC/ESP3)</li> <li>▪ KNX IP</li> <li>▪ IEC61850 MMS &amp; GOOSE</li> <li>▪ EtherCAT</li> </ul>

\*"Inside App only" means the Interface can only be use inside an additional runtime app


Terminology, Roles, and Tasks in Security Processes

# The “Automation Pyramid”



Applicable Security Laws and Standards

# IEC 62443: IT-Security for Industrial Automation Control Systems



**Authentication**

- User accounts
- Authentication of credentials
- Authorization

**Confidentiality**

- Use of secure protocols
- Secure remote maintenance
  - Cryptography
- Protection of expertise

**Integrity**

- Principle of least privilege
- Defense of depth
- Network segmentation

**Availability**

- Monitoring and attack detection
- Tamper protection



**IEC 62443**

**Industrial Automation  
Basis Standard**



# IEC 62443: IT-Security for Industrial Automation Control Systems



The image displays two TUV SUD certificates and a photograph of a PLCnext Control unit. The left certificate (No. Q4B 029429 0007 Rev. 00) certifies the holder, PHOENIX CONTACT GmbH & Co. KG, for the Secure Product Development Lifecycle. The right certificate (No. IITS2 029429 0027 Rev. 00) certifies the same holder for IACS components, specifically PLCnext Control units with Security Profil active. The photograph shows a rack-mounted PLCnext Control unit with various ports and a terminal block.

**CERTIFICATE**  
No. Q4B 029429 0007 Rev. 00

Holder of Certificate: PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
GERMANY

Factory(ies): PHOENIX CONTACT Electronics GmbH  
Industry Management and Automation  
Business Unit Control Systems  
Dingensauer Strasse 30, 31812 Bad Pyrmont, GERMANY  
PHOENIX CONTACT Software GmbH  
Langenbruch 9, 32657 Lemgo, GERMANY

Certification Mark: 

Scope of Certificate: Secure Product Development Lifecycle

Applied Standard(s): IEC 62443-4-1:2018  
PPP 15002A:2018 (IEC 62443-4-1 Full Process Profile)

Report No.: 18CR015007

Valid until: 2021-07-29

Date: 2018-08-01  
(Andreas Barwald)

Page 1 of 1  
TUV SUD Product Service GmbH • Certification Body • Ridlerstraße 65 • 80339 Munich • Germany

**CERTIFICATE**  
No. IITS2 029429 0027 Rev. 00

Holder of Certificate: PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
GERMANY

Certification Mark: 

Product: IACS components

Model(s): PLCnext Control  
(Configuration: Security Profil active)  
AXC F 1152, AXC F 2152, AXC F 3152

Tested according to: IEC 62443-4-1:2018  
IEC 62443-4-2:2019  
PPP 15003B:2021 (IEC 62443-4-1: Full ML3 Process Profile)

The secure development lifecycle and the resulting product(s) were assessed on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. See <http://www.tuvsud.com/ps-cert> for details.

Test report no.: 21CR035047  
Valid until: 2024-10-20

Date: 2021-11-19  
(Nadia Patricia Stefan)

Page 1 of 1  
TUV SUD Product Service GmbH • Certification Body • Ridlerstraße 65 • 80339 Munich • Germany



The graphic features a large white hexagonal logo on a black background. Below the logo, the text 'IEC 62443' is written in large blue letters, followed by 'Industrial Automation Basis Standard' in white italicized font.

# IEC 62443

*Industrial Automation  
Basis Standard*



Confidential





PLCnext Ecosystem – PLCnext Control

# PLCnext Control extension possibilities




- Modular expandability of the controller through left-side expansion modules on the PCI express interface via a corresponding bus socket
- Unlimited expansion possibilities with Axioline IO



Countless possibilities in hardware variance

# PLCnext Control


PLCnext Technology   
Designed by PHOENIX CONTACT



new

## PLCnext Control Extension

Control functionality can be easily extended with left-handed modules



Axioline Smart Elements

# Automate smart and economically



## Ready for automation

All necessary functionalities  
incl. Safety and IO-Link

DI

SDI

AI

IO-Link

INC

DO

SDO

AO


RS485

CNT




I/O solutions for process industry

# Axioline F – Monitoring and Optimization




- Extreme condition temperature range
- IECEx/ATEX zone 2 certification
- Intrinsically safe
- HART communication
- NAMUR functionality

**Side process automation:**  
Focus on monitoring and optimization




I/O solutions for process industry

# Axioline P – high availability with hot-swap



- PROFINET S2 redundancy
- Hot-swap
- Installation in zone 2
- Connection to zone 0/1
- HART communication
- NAMUR functionality

**Core process automation:**  
 Connecting the field level to the control room




## PLCnext Ecosystem – PLCnext Control

# Portfolio PLCnext Control Extensions




PLCnext Technology Ecosystem – Artificial Intelligence

## PLCnext Extension AXC F XT ML 1000




- Additional Machine Learning accelerator
- Google Edge TPU ML accelerator
- 4 trillion operations per second (TOPS)
- Tensorflow Lite or AutoML
- Approvals
  - UL (Hazloc), CUL
- Temperature range: -20°C up to 55°C
- Due to 64Bit architecture available with AXC F 3152



# The open ecosystem for limitless automation



**Safety**  
with PLCnext Control




PLCnext Control

Discover flexible automation










# PLCnext Control Extension SPLC 1000



PLCnext Extension AXC F XT SPLC 1000

<b>Core</b>  <b>2 x Cortex M4</b>	<b># of Profisafe devices</b>  <b>32</b>	<b>Temperature</b>  <b>-25°C - 60°C</b>
<b>Width</b>  <b>45mm</b>	<b>Approvals</b>  <b>UL, CUL, etc</b>	<b>C Functions</b> <b>C</b> <b>Reloadable</b>

# PLCnext Safety Extension AXC F XT SPLC 1000

- Scalable PLCnext Safety Control
- Reloadable C-Functions, e.g.
  - Complex safety algorithm
  - Safety Machine Learning
  - Automatic certification
- Adaptable Safety Communication, e.g.
  - OPC UA Safety (M2M)
  - PROFIsafe (M2D)
  - Vendor specific
- Approvals
  - SIL3, PLe
  - UL (Hazloc), CUL
  - IEC Ex, ATEX




- Scalable PLCnext Control
- Open ecosystem for limitless automation
  - IEC 61131-3, C, C++, C#, Matlab
  - OPC UA, MQTT, ...
- Open communication standards
- Security by design
- Built-in cloud connectivity



PLCnext Technology - Scalable Safety PLC


# AXC F XT SPLC 1000 – Modular Safety PLC



- Decentralized Small Safe PLC
- Connectable to PLCnext Controls as extension Modul
- Supported Safety Protocols:
  - PROFI-safe V2.61 (32 instances)
- Connectable to higher-layer SPLC as F-Device and via new OPC UA Safety Protocol



# PLCnext Control RFC 4072R for Profinet S2 Redundancy




The image shows a PLCnext Control RFC 4072R device. The front panel features a color display showing the 'RFC 4072R' configuration menu with options for 'Projektname', 'PN Controller', 'OPC UA', and 'Redundancy' (set to 'First Primary'). The device has various ports including RUN/PROG, STOP, MRESET, SD-CARD, USB, LAN 1-3, and SYNC. It is designed by PHOENIX CONTACT.


Feature	Specification
CPU	Intel i5 6300U 2 x 2,4 GHz processor
Random Access Memory	4 GB DDR 4 dual channel RAM
ETH-MAC interface	3 ETH-MAC interfaces (2 x 1 Gbit, 1 x 100 Mbit switched)
Synchronization interface	minimal switch-over time 5ms
Power supply	Dual interface
Temperature	0°C - 55°C




# Software Redundancy for 2152 and 3152 with software function blocks



- Both Profinet IO-controllers are connected to all Profinet IO-devices at the same time.
- One has the role of the Primary the other Backup
- This communication is done via an UDP/IP based protocol.
- Typical system switch-over time: Minimum 300ms



- Media Redundancy Protocol (MRP) according to IEC62439:
- One Switch has the role of the MRP-manager. All other devices in the ring structure must support the MRP-client function.
- Typical switch-over time 200ms.




# PLCnext Control for Edge Computing




# Edge Computing

- Cloud computing has revolutionized how people store and use their data, but...
- Latency, bandwidth, security or a lack of offline access can be problematic
- To solve this problem, users need robust, secure and intelligent on-premise infrastructure for edge computing
- When data is physically located closer to the user who connect to it, information can be shared quickly, securely and without latency




# Edge functions within PLCnext Control






# Edge functions within PLCnext Control



## Edge Computing - Use cases



**Data collection** from sensors, actuators and PLCs.  
Usage of typical protocols like OPC UA, Profinet, Modbus TCP & RTU and much more.



**Data storage, processing and dashboards.**  
A wide range of rules and statistics can be used with Influx DB. Visualization is supported with Influx DB Chronograf.



**Sending data to superordinated- and Cloudsystems.**  
Integrated cloud connection and support of a wide range of communication e.g. via Node Red



# enhanced connectivity – Intelligent Networking


## PLCnext Control – AWS Qualified

The screenshot displays the AWS Qualified Device page for Phoenix Contact. The page features the AWS logo and 'qualified device' branding on the left. The main content area is titled 'Qualified Devices (3)' and lists three Programmable Logic Controller (PLC) models:

- PROGRAMMABLE LOGIC CONTROLLER (PLC)**  
AWS IoT Core  
EPC 1502  
Combining the OT and IT world
- PROGRAMMABLE LOGIC CONTROLLER (PLC)**  
AWS IoT Core  
EPC 1522  
Combining the OT and IT world
- PROGRAMMABLE LOGIC CONTROLLER (PLC)**  
AWS IoT Greengrass  
Phoenix Contact AXCF2152  
PLCnext Control for the direct control of Axioline F I/Os, with two Ethernet interfaces. Complete with connector and bus base module.



Below the list, three physical images of the PLC units are shown, each with an 'aws qualified device' badge. The first two are EPC 1502 and EPC 1522, and the third is the AXCF2152. A fourth image of a larger PLC unit is partially visible on the right.

# Device and Update Management with Edge Computing




## Device and Update Management

# Benefits of a Device and Update Management





# Process steps of Device and Update Management



PLCnext Technology – New Starterkit


# Start now and become a part of PLCnext Technology



PLCnext Technology   
Designed by PHOENIX CONTACT  
Ecosystem for limitless automation


GETTING STARTED  
starterkit.plcnextcommunity.com

Getting started



Online

Hardware



PLCnext Control & Axioline Smart Element


starterkit.plcnextcommunity.com



[www.plcnexttechnology.be/nl/starterkit](http://www.plcnexttechnology.be/nl/starterkit)  
359,-€




# The All Electric Society:





# Data flow MINT Advanced



CINI4.0



# CINI4.0 Conference Day

16/06/2022, Gent



## PLCnext : an open source IIOT-ready PLC

Hugo Van Rillaer

[hvanrillaer@phoenixcontact.be](mailto:hvanrillaer@phoenixcontact.be)

Questions ? Demo ? -> Phoenix Contact